

## DAFTAR PUSTAKA

- [1] P. Velineni, J. Suresh, C. N. Kumar, and M. Suresh, “Design of Pneumatic *Gripper* for Pick and Place Operation (Four *Jaw*),” *Int. Res. J. Multidiscip. Technovation*, vol. 2, no. 2, pp. 1–8, 2020, doi: 10.34256/irjmt2021.
- [2] A. Jafarov and M. Mustafayev, “Designing and testing multi-functional robot *gripper*,” 2019, [Online]. Available: <https://odr.chalmers.se/handle/20.500.12380/300766>.
- [3] Z. Long, Q. Jiang, T. Shuai, F. Wen, and C. Liang, “A Systematic Review and Meta-analysis of Robotic *Gripper*,” *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 782, no. 4, 2020, doi: 10.1088/1757-899X/782/4/042055.
- [4] S. D’Avella, P. Tripicchio, and C. A. Avizzano, “A study on picking objects in cluttered environments: Exploiting depth features for a custom low-cost universal jamming *gripper*,” *Robot. Comput. Integr. Manuf.*, vol. 63, no. June, 2020, doi: 10.1016/j.rcim.2019.101888.
- [5] I. Vaani, S. Pal, V. Indu, and P. Sreedharan, “Optimal Force Control and Analysis of Soft Pneumatic Actuator,” *2019 2nd Int. Conf. Intell. Comput. Instrum. Control Technol. ICICICT 2019*, pp. 501–506, 2019, doi: 10.1109/ICICICT46008.2019.8993383.
- [6] R. Bhaskar, J. Butt, and H. Shirvani, “Investigating the Properties of ABS- Based Plastic Composites Manufactured by Composite Plastic Manufacturing,” *J. Manuf. Mater. Process.*, vol. 6, no. 6, 2022, doi: 10.3390/jmmp6060163.
- [7] S. Kumar and K. P. Rajurkar, *Advances in Manufacturing Systems*. 2020.
- [8] S. Bisht, A. Jha, and B. Rautela, “Experimental Performance Analysis of Pneumatically Driven Mechanical Robotic Arm for Pick and Place Operation,” *Int. J. Emerg. Technol.*, vol. 6, no. 1, pp. 37–42, 2015, [Online]. Available: <http://www.researchtrend.net/ijet/ijet61/7 SHWETA BISHT.pdf>.

- [9] M. B. Anthony Mabanta, J. P. Pabillaran, and etal B. Engr Maridee Adiong, “Robotic Arm Pick and Place System.”
- [10] F. Y. Chen, “Gripping mechanisms for industrial robots. An overview,” *Mech. Mach. Theory*, vol. 17, no. 5, pp. 299–311, 1982, doi: 10.1016/0094-114X(82)90011-8.
- [11] S. Pukkella, V. S. Babu, and K. M. Abubacker, “Design and Development of Pick and Place Robotics Arm,” *Int. J. Adv. Eng. Res. Dev.*, vol. 4, no. 04, pp. 4801–4807, 2017, doi: 10.21090/ijaerd.ee014.
- [12] T. Deaconescu and A. Deaconescu, “Pneumatic muscle-Actuated adjustable compliant *gripper* system for assembly operations,” *Stroj. Vestnik/Journal Mech. Eng.*, vol. 63, no. 4, pp. 225–234, 2017, doi: 10.5545/sv-jme.2016.4239.
- [13] K. Ohara, R. Iwazawa, and M. Kaneko, “Modeling and Analysis of a High- Speed Adjustable Grasping Robot Controlled by a Pneumatic Actuator,” *Robotics*, vol. 11, no. 1, pp. 1–16, 2022, doi: 10.3390/robotics11010027.
- [14] S. P. kumar, K. S. Varman, and R. B. murugan, “Design and Implementation of multi handling Pick and Place Robotic Arm,” *Int. J. Eng. Trends Technol.*, vol. 33, no. 3, pp. 164–166, 2016, doi: 10.14445/22315381/ijett-v33p230.
- [15] N. Abdul Wahab and J. Thangaraj, “Automation of Pick and Place Operation in Contact Lens Manufacturing,” *Elektr. J. Electr. Eng.*, vol. 17, no. 2, pp. 25–29, 2018, doi: 10.11113/elektrika.v17n2.95.
- [16] C. Mass, S. Dagstuhl, S. Albers, and S. Diehl, “Volume 3, Issue 12, December 2013,” vol. 3, no. 12, p. 14947, 2013.
- [17] J. C. Sagot, V. Gouin, and S. Gomes, “Ergonomics in product design: Safety *factor*,” *Saf. Sci.*, vol. 41, no. 2–3, pp. 137–154, 2003, doi: 10.1016/S0925-7535(02)00038-3.